



FTU-TK01

Reggefiber FTU - standard

Article number: 566040

Date: 30-03-2020



Bill of materials

Article number	Quantity	Unit
<u>566042</u>	1	piece
<u>566047</u>	1	piece

Product characteristics

Height	100 mm
Width	98.4 mm
Depth	29.5 mm
Material	Plastic
RAL-number	9010
Colour	White
Number output cables	2
Diameter input cables	5.0/8.0 mm
Type of coupling	Fusion splice
Patch possibility	Yes
Number of patch positions	2
Type adapter	SC
Splice possibility	Yes
Max. number of splice trays	1
Number of pigtails	1
Including pigtails	Yes
Suitable for number of fibers	2



Unit	1	piece(s)
Weight (kg)		0.085

Optical specification

Fibre type	ITU-T G.657.A1
------------	----------------

Environmental specification

Degree of protection (IP)	IP40
Operating temperature	-20/65 °C
Transport and storage temperature range	-20/50 °C

Other specification

Fibre management	Single circuit
Pigtails stripped	Yes
Splice protection	ANT or heat shrink mini



Article number: 566042

Date: 30-03-2020

Accessories for distribution boxes contain cable strain relief clamps and tube glands. To achieve flexibility and modularity of the final product one need to order the accessory sets separately from the distribution boxes.



Product characteristics

Material	Plastic
Colour	White




FTU-TK01

pigtail G.657.A1 blue SC/APC I1/I2:1.0/0.225 ACW

Article number: 566047

Date: 30-03-2020



Product characteristics

Type	Conductor pigtail
Core type	Dry buffer 0.9 mm
Colour	Blue
Length	1.0 m
Strip length	775 mm
Type of connector	SC
APC-version	Yes
Angle for APC connector	8
Weight (kg)	0.010

Optical specification

Fibre type	Singlemode
IL Grade according IEC 61753	IL-Grade C
RL Grade according IEC 61753	RL-Grade 1



Environmental specification

Suitable for service environments according IEC 61753

U - Uncontrolled environment

Other specification

Boot colour

Green